

150 Tack Tank

LeeBoy



The 150 Tack Distributor ideally serves the paving contractor dedicated to smaller projects. With a conservative 150 gallon capacity tank, this solution still boasts of many features and functions of the larger units. Inclusive of a powerful Honda engine, the user-friendly design can either be trailer or skid mounted. Multiple additional options including in-cab controls or overnight heating can further enhance the end user's experience.

Performance Features:

- 150 Gallon (568 l) Capacity Tank
- 4.8 hp (3.6 kw) Honda Engine
- 6' (1.8 m) Wand with On/Off Valve
- 40' (12.19 m) Heavy-Duty Recoil Hose Reel
- 2,771 lbs (1,256 kg) Loaded Weight
- Rear Tank Sampling Valve
- Two 54,000 BTU Propane Burners
- Trailer or Skid-Mount Configurations
- Optional Accessories Available



150 Tack Distributor Specifications



Tank Size	150 gallons (567.8 l)
Dimensions (Trailer Configuration)	<ul style="list-style-type: none"> - Length: 11' (3.35 m) - Width: 6' 6" (1.98 m) - Height: 7' 2" (2.18 m) - Shipping Weight: 1,556 lbs (705.7 kg)
Dimensions (Skid Mount Configuration)	<ul style="list-style-type: none"> - Length: 6' 4" (1.93 m) - Width: 4' (1.21 m) - Height: 6' 6" (1.98 m) - Shipping Weight: 900 lbs (408 kg)
Engine	Honda – 4.8 hp (3.6 kw)
Capacities	- Fuel: 1 gallon (3.79 l)
Tank Dimensions	<ul style="list-style-type: none"> - Length: 42.25" (1.07 m) - Width: 34" (.86 m) - Height: 30" (.76 m)
Asphalt Pump	- Specially designed 7 gallons per minute (26.5 lmp) pump
Heat System	<ul style="list-style-type: none"> - Two 54,000 BTU propane burners - One start burner - 30 lbs (13.6 kg) propane fuel tank
Temperature Gauge	- 50 - 300° F (10 - 149° C)
Flush Tank	- 7 gallons (26.5 l) tank with suck back valve

Hose and Reel	- .5" x 40' (13 mm x 12.19 m) heavy-duty recoil hose reel
Wand	<ul style="list-style-type: none"> - 6' (1.829 m) wand with cold handles - On/off valve - Removable spray tip
Fill Spout	10" x 10" (254 x 254 mm) with splash plate
Clean Out	- 4" (102 mm)
Access Valve	- 1" (25 mm)
Optional Equipment	<ul style="list-style-type: none"> - Electric start (available on Honda-Gas and Hatz-Diesel engine) - 5 hp Hatz diesel engine (pull start) - Insulated tank - Auto ignition burners (only available with electric start engine) - Auto ignition burners with outfire protection (only available with electric start engines) - 8' (2.4 m) spray bar - Spray bar lift (only available on skid-mounted unit) - In-truck controls (requires 8' spray bar option) - Overnight heater - Surge brakes (only available on trailer mounted unit) - 2inch ball hitch



VT LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300
www.LeeBoy.com

LeeBoy and the LeeBoy logo are registered trademarks of VT LeeBoy, Inc. Equipment model names, slogans and subsidiary logos appearing in this collateral may be registered trademarks or the trademarks of VT LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy reserves the right to modify at any time. © 2019 VT LeeBoy, Inc. All rights reserved. BR-4001.2-EN

